

Certificate of shape stability

1. Ref. transp. packaging unit: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

2. Ref. measuring report: Wienerberger nv - 20181009012

B. Company: Wienerberger nv

4. Performed test: Acceleration test according to: Be RD of April 27th 2007, EUMOS 40509,

5. Date: 9/10/2018 EN12195-1:2010

6. Description of the tested transport packaging unit

Description

A wooden 1100x1100 pallet containing 13 layers. In total there are 936 bricks BEE 188X88X48 on the pallet. There are two vertical straps in the BP-direction.

Primary packaging: / Secundary packaging: /

<u>Tertiary packaging:</u> Stretch film: ☐ Stretch hood: ☐ Shrink hood: ✔ Straps: ✔

Add transport packaging: /

Anti slip up the pallet:

Anti slip up on layer(s):


Stacking pattern: Interlocked

 Pallet_type:
 1100x1100
 # Layers:
 13

 Height [mm]:
 710
 Weight[kg]:
 1170

<u>Length - LP [mm]:</u> 1100 <u>Width - BP [mm]:</u> 1100

Name and signature responsible of the packaging:



Picture in the BP-direction after the test.







10. Conclusions:

The tested load unit is shape stable in the BP-direction at 0.5g under the specified test conditions. The tested load unit is shape stable in the LP-direction at 0.5g under the specified test conditions.

Wafelstraet 16 8540 Dientik België

11. Name and signature responsable of the test: Ing. J. Dendauw



TEST REPORT of the ACCELERATION TEST based on RD of April 27th 2007, EN12195:2010, EUMOS 40509

Ref. transp. packaging unit: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

Ref. measuring report: Wienerberger nv - 20181009012

Specifications of the test

Client

<u>Company:</u> Wienerberger nv <u>Address:</u> Kapel Ter Bede 121

8500 Kortrijk

België

<u>Contact pers.:</u> Danny Wallaert Tel. nr.: +32 (0) 56 24 96 27

<u>Fax nr.:</u> - Mob. nr.: -

<u>E-mail:</u> Danny.Wallaert@wienerberger.com

Test details:

Test facility: ESTL nv, wafelstraat 45, 8540 Deerlijk, België

<u>Test responsible:</u> Ing. Jelle Dendauw

Test equipment: MJ1500 acceleration bench

<u>Test date:</u> 9/10/2018

People attending: Jelle Dendauw (ESTL), Danny Wallaert (Wienerberger)

Temperature [°C]: 20
Rel. humidity [%]: 50

<u>Load conditions:</u> Sliding of the load unit is prevented mechanically.

Attached documents to the report: /

Goal of the acceleration test

According to the Belgian RD* of April 27th 2007, EUMOS 40509 and the EN12195:2010, a load securing layout has to be capable of withstanding certain forces of inertia. These forces amount to 0,8g in forward direction, 0,5g in rearward direction and 0,5g in the sideward directions. The acceleration test allows for an unambiguous assessment of a certain load unit, secured in a specified manner, with the rules and regulations of the Belgian RD.

A load unit is placed on a platform and is secured in the correct orientation and according to a specified securing layout. The platform is then accelerated at 0,8g or 0,5g to imitate the influence of the forces of inertia originating from the forward deceleration as prescribed in abovementioned RD. The stability of the load unit is then assessed. If the load unit is deemed stable, it is rotated 90 degrees, together with the securing layout. Next, the platform is accelerated at 0,5g to imitate the influence of the forces of inertia originating from the sideward acceleration prescribed in abovementioned RD. After this test the stability of the load unit is assessed once again.











Reference 20181009/012

Author Dendauw Jelle

Contact: Danny Wallaert

Date: 9/10/2018

Company: Wienerberger nv Pallet name: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

Conclusions













Reference 20181009/012 **Company:** Wienerberger nv

Author Dendauw Jelle

Contact: Danny Wallaert

Date: 9/10/2018

Pallet name: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

General remarks and conclusions

Conclusions:

- The pallet is behaving shape stable at 0,5g in the LP-direction following EUMOS40509.
- The pallet is behaving shape stable at 0,5g in the BP-direction following EUMOS40509.

Hood specifications

Hood reference: Technosales Thickness [µm]: 110 Hood Type: Stretch hood Initial dimensions [mm]x[mm]: 800_X 700 Vertical stretch [%]: Hor. stretch long side [%]: Hor. stetch short side [%]: Configuration of the hood: **V**











Reference 20181009/012

Author Dendauw Jelle

Contact: Danny Wallaert

Date: 9/10/2018

Company: Wienerberger nv Pallet name: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

Pallet specifications

Name of the pallet: Wienerberger 1100x1100 PER RETRO 188X88X48 936pcs

A wooden 1100x1100 pallet containing 13 layers. In total there are 936 bricks BEE 188X88X48 on the pallet. There are two vertical straps in the BP-direction.

Pallet type: 1100x1100

Stacking pattern: Interlocked

Layers: 13 Cases per layer:

Tie sheet between load and pallet:

Tie sheet on top of layer(s):


<u>LP [mm]:</u> 1100 <u>BP[mm]:</u> 1100 <u>Weight [kg]:</u> 1170 <u>Height [mm]:</u> 710



Primary packaging

Name.: /

Type:



Name: /
Theor. head space [mm]: 0
Gross weight [kg]: 0
Compression force [N]: 0
Fluting type:
Prim units per sec. unit: 0

Additional packaging
/